



Telecamere S-Sight 2 MP



Caratteristiche: 25/30 fps, H.265, SD card fino a 128Gb, WDR Digitale, 3D-DNR, BLC, HLC, ROI, Privacy mask, Motion detection, 2 streams, IP 67, Alimentazione DC12V/POE.

General video analytics: Camera tampering, Smart search.

Standard video analytics: Line crossing, Sterile Area.



DI-320IPSN-28 | DI-320IPSN-28-G



DI-320IPSN-36



DI-320IPS-VF | DI-320IPSN-VF-G



Ottica	2.8mm (107°)	3.6mm (87.3°)	2.8-12mm Vari-Focal (88°-34.8°)
Distanza IR	20m (1 High Power IR LED)	20m (1 High Power IR LED)	40m (3 High Power IR LED)
Audio	Microfono incorporato	Microfono incorporato	Microfono incorporato
Alimentazione	DC12V/~400mA / PoE/~5.2W	DC12V/~420mA / PoE/~5.4W	DC12V/~900mA / PoE/~10W
Staffe/box di giunzione	G	G	F

I2-320IPSN-28 | I2-320IPSN-28-G



I2-320IPSN-36



I4-320IPSN-VF



Ottica	2.8mm (107°)	3.6mm (87.3°)	2.8-12mm Vari-Focal (94°-35.7°)
Distanza IR	20m (1 High Power IR LED)	20m (1 High Power IR LED)	40m (2 High Power IR LED)
Audio	-	-	-
Alimentazione	DC12V/~420mA / PoE/~5.4W	DC12V/~420mA / PoE/~5.4W	DC12V/~780mA / PoE/~7.4W
Staffe/box di giunzione	A	A	B

Telecamere S-Sight 4 MP



Caratteristiche: 25/30 fps, H.265, SD card fino a 128Gb, WDR Digitale, 3D-DNR, BLC, HLC, ROI, Privacy mask, Motion detection, 2 streams, IP 67, Alimentazione DC12V/POE.
 General video analytics: Camera tampering, Smart search.
 Standard video analytics: Line crossing, Sterile Area.

	DI-340IPSN-28 DI-340IPSN-28-G	DI-340IPS-36	DI-340IPSN-MVF DI-340IPS-MVF-G
			
Ottica	2.8mm (110°)	3.6mm (89°)	2.8-12mm Motorized Vari-Focal con Auto Focus (94°-35.7°)
Distanza IR	20m (1 High Power IR LED)	20m (1 High Power IR LED)	40m (3 High Power IR LED)
Audio	Microfono incorporato	Microfono incorporato	Microfono incorporato
Alimentazione	DC12V/~400mA / PoE/~5.2W	DC12V/~400mA / PoE/~5.2W	DC12V/~900mA / PoE/~10W
Staffe/box di giunzione	G	G	F

	I2-340IPSN-28 I2-340IPSN-28-G	I2-340IPS-36	I4-340IPS-MVF
			
Ottica	2.8mm (110°)	3.6mm (89°)	2.8-12mm Motorized Vari-Focal con Auto Focus (94°-35.7°)
Distanza IR	20m (1 High Power IR LED)	20m (1 High Power IR LED)	40m (2 High Power IR LED)
Audio	-	-	-
Alimentazione	DC12V/~420mA / PoE/~5.4W	DC12V/~420mA / PoE/~5.4W	DC12V/~780mA / PoE/~7.4W
Staffe/box di giunzione	A	A	B

Telecamere S-Sight 8 MP



Caratteristiche: 25/30 fps, H.265, SD card fino a 128Gb, WDR Digitale, 3D-DNR, BLC, HLC, ROI, Privacy mask, Motion detection, 2 streams, IP 67, Alimentazione DC12V/POE.
 General video analytics: Camera tampering, Smart search.
 Standard video analytics: Line crossing, Sterile Area.

	DI-380IPS-28	DI-380IPS-MVF	I4-380IPS-28	I4-380IPS-MVF
				
Ottica	2.8mm (112°)	2.8-12mm Motorized Vari-Focal con Auto Focus (102.7°- 32.2°)	2.8mm (112°)	2.8-12mm Motorized Vari-Focal con Auto Focus (102.7°- 32.2°)
Distanza IR	20m (1 High Power IR LED)	40m (3 High Power IR LED)	40m (2 High Power IR LED)	40m (2 High Power IR LED)
Audio	Microfono incorporato + 1 IN	Microfono incorporato + 1 IN	1 IN	1 IN
Alimentazione	DC12V/~400mA / PoE/~5.2W	DC12V/~900mA / PoE/~10W	DC12V/~420mA / PoE/~5.4W	DC12V/~780mA / PoE/~7.4W
Staffe/box di giunzione	G	F	B	B

IP HD / Staffe/box di giunzione per telecamere

A - Bullet I2



B - Bullet I4



C - Bullet I6



D - Fisheye



E - Mini dome



F - Turret/Dome vari-focal



G - Turret/Dome ottica fissa



H - Anti-vandal dome vari-focal



I - Anti-vandal dome ottica fissa



L - Intelligent Auto-Tracking PTZ

